

# S.T.O.U. FARM 10W30

**Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.**

## APPLICATIONS

This multigrade oil is advised for the lubrication of charged and uncharged diesel engines (TURBO), 4-stroke gasoline engines and LPG-engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines for off-highway equipment.

## FEATURES

Anti-wear and oxidation stability : proven protection of critical parts.  
Cold start: excellent fluidity at low temperature.

## SPECIFICATION LEVEL

<b>ACEA</b>	E3	<b>MF</b>	M 1135
<b>ALLISON</b>	C4 (Agriculture applic.)	<b>MF</b>	M 1139
<b>API</b>	CG-4	<b>MF</b>	M 1143
<b>API</b>	GL-4	<b>MF</b>	M 1144
<b>API</b>	GL-5 (Low speed/high torque)	<b>NH</b>	NH 030C
<b>API</b>	SF/CE	<b>NH</b>	NH 410B
<b>CASE</b>	MAT 3525	<b>NH</b>	NH 420A
<b>CASE</b>	MAT 3526	<b>ZF</b>	TE-ML 03A
<b>FORD</b>	ESN-M2C-159B/C	<b>ZF</b>	TE-ML 05K
<b>FORD</b>	ESN-M2C134 C/D	<b>ZF</b>	TE-ML 06A
<b>FORD</b>	ESN-M2C159 B/C	<b>ZF</b>	TE-ML 06B
<b>FORD</b>	FNH 82009201	<b>ZF</b>	TE-ML 06C
<b>JD</b>	J27	<b>ZF</b>	TE-ML 07B
<b>JD</b>	J20C	<b>ZF</b>	TE-ML 07D
<b>MF</b>	M 1145		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.869
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	75
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11.4
Viscosity index	ASTM D2270		144
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**