

# OEM SPECIFIC

## 10W40 S3

*This is a full synthetic lubricant based on carefully selected very high quality base oils. This "long-drain" oil is engineered to provide outstanding lubrication to modern, high performance diesel engines.*

### APPLICATIONS

*This oil is suitable for Euro IV, Euro V and mandatory for the latest SCANIA Euro VI engines. Due to the high ash content, this oil is not suitable for most engines and vehicles equipped with a particulate filter.*

### FEATURES

*Emission compatibility : superior emission reduction.*

*Total engine protection : outstanding engine cleanliness and durability.*

*Cold start : very good fluidity at low temperature.*

### SPECIFICATION LEVEL

<b>ACEA</b>	E4-12	<b>MB</b>	228.5
<b>ACEA</b>	E7-12	<b>MTU</b>	Type 3
<b>API</b>	CF	<b>RENAULT</b>	RD-2
<b>CUMMINS</b>	CES 20072	<b>RENAULT</b>	RLD
<b>DAF</b>	EXTENDED DRAIN	<b>RENAULT</b>	Approval RLD-2
<b>DEUTZ</b>	DQC-III-10	<b>RENAULT</b>	RXD
<b>MACK</b>	Approval EO-N	<b>VOLVO</b>	Approval VDS-3
<b>MAN</b>	M3277		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	86.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.3
Viscosity index	ASTM D2270		155
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	16.1
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Sulfated Ash	ASTM D874	Mass %	1.9
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION**<sup>®</sup>