

# ACTIVE DEFENCE

## SAE 50 SF/CD

*Monograde engine oil for the lubrication of gasoline and diesel engines of passenger cars, with or without turbo. This oil is characterized by a combination of good detergent and dispersant properties, together with a low ash content.*

### APPLICATIONS

*This oil is suitable for the lubrication of gasoline and diesel engines from 1980 to 1989.*

### FEATURES

*Total engine protection : engine protection and cleanliness.*

### SPECIFICATION LEVEL

<b>API</b>	SF/CD	<b>MIL</b>	MIL-L-46152 B
<b>MB</b>	226.0		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.898
Kinematic viscosity at 40°C	ASTM D445	mm²/s	204
Kinematic viscosity at 100°C	ASTM D445	mm²/s	17,8
Viscosity index	ASTM D2270		95
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	5,0
Pour point	ASTM D6892	°C	-24
Flash Point COC	ASTM D92	°C	250

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**