

# UNIVERSAL 2T

**Oil for air-cooled 2-stroke gasoline engines. Suitable for machines where the reservoir is filled with a mixture of gasoline and oil, and for those with separate reservoirs. This oil is easily miscible with gasoline and ensures a good protection of the pistons and segments from overheating.**

## APPLICATIONS

*This oil is applicable for all air cooled 2-stroke gasoline engines with a dilution content of 2% (1 to 50) and 4% (1 to 25). This according to the constructor's requirements.*

## FEATURES

*Engine protection : excellent engine performance.  
Corrosion protection : adequate corrosion protection.*

## SPECIFICATION LEVEL

**API**                      **TC**

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.887
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	55,3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8,3
Viscosity index	ASTM D2270		121
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	1,1
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	106

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**