

# SNOW SCOOTER 2T TC-W3

*This is a mineral, top quality 2 stroke motor oil, specifically developed for being used in snowscooters, working in low ambient temperatures. Its ashless composition prevents the formation of deposit, pre-ignition and spark plug fouling. High protection against rust and corrosion.*

## APPLICATIONS

*This product is primarily intended for 2-cycle snowmobiles with high power output. It is recommended as an injector oil or at a 50:1 ratio in carburetted or direct fuel injection systems.*

## FEATURES

*Engine protection : outstanding engine cleanliness and durability.  
Corrosion protection : adequate corrosion protection.*

## SPECIFICATION LEVEL

**NMMA** TC-W3

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.877
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	49.1
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.88
Viscosity index	ASTM D2270		129
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	6.2
Pour point	ASTM D6892	°C	-36
Sulfated Ash	ASTM D874	Mass %	0
Flash Point COC	ASTM D92	°C	105
Brookfield viscosity at -25°C	ASTM D2983	mPa.s	5740
Colour	VISUAL		DarkBlue

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION**<sup>®</sup>