

MOTOR OIL CF-4/SG SAE 10W

Universal mineral oil of high quality, suitable for diesel engines (supercharged or naturally aspirated) and gasoline engines operating in cold climatic conditions.

APPLICATIONS

This oil is particularly recommended for fixed diesel engines, material for public works and mixed fleets of trucks and cars. It can also be used as hydraulic oil (eg. Caterpillar)

FEATURES

Total engine protection : performance in keeping the engine clean.

SPECIFICATION LEVEL

API	CF-4/SG	MIL	MIL-L-2104 E
MB	227.0	MIL	MIL-L-46152 E

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	41
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6,7
Viscosity index	ASTM D2270		118
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	6.0
Pour point	ASTM D6892	°C	-24
Sulfated Ash	ASTM D874	Mass %	0,7
Flash Point COC	ASTM D92	°C	212

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION[®]