

NEW ENERGY

75W80 MULTI VEHICLE

This is a high quality transmission oil, suitable for nearly all manual gearboxes of passenger cars. It is especially suitable as a replacement for specific OEM original oils and reduces the complexity and storage of gearbox oils. Tested under strict conditions, this oil satisfies the general performance requirements of most car makers and models, in all weather conditions.

APPLICATIONS

Tested under strict conditions, this oil meets the general performance requirements of most brands and models in all weather conditions.

FEATURES

Frictional properties : very smooth gear shifting, no vibration.

Anti-wear protection : significantly extended transmission life.

Extended oil life : proven resistance to oil degradation.

SPECIFICATION LEVEL

| | | | |
|--------------|--------------|---------------|----------|
| API | GL-4 + | MB | 235.10 |
| FIAT | 9.55550-MX3 | NISSAN | MT-XZ |
| FIAT | 9.55550-MZ1 | PSA | B71 2330 |
| FORD | WSD-M2C200-D | PSA | 9730 A8 |
| FORD | ESD-M2C186-A | VOLVO | 97308 |
| GM | 1940182 | VOLVO | 97309 |
| GM | 1940768 | VOLVO | 97310 |
| HONDA | MTF 94 | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average result |
|-------------------------------|------------|--------------------|----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.871 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 45.8 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 9.1 |
| Viscosity index | ASTM D2270 | | 185 |
| Pour point | ASTM D6892 | °C | -45 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | 142.000 |
| Flash Point COC | ASTM D92 | °C | 205 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®