

LIFE EXTENSION

80W90 GL 5

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

FEATURES

Frictional properties : easy gear shifting.

Anti-wear protection : long transmission life.

SPECIFICATION LEVEL

API	GL-5	ZF	TE-ML 16C
MAN	342 M-1	ZF	TE-ML 19B
MAN	342 M-2	ZF	TE-ML 07A
MIL	MIL-L-2105 C	ZF	TE-ML 12E
MIL	MIL-L-2105 D	ZF	TE-ML 16B
ZF	TE-ML 05A	ZF	TE-ML 17B

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.896
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	147
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.7
Viscosity index	ASTM D2270		99
Pour point	ASTM D6892	°C	-33
Brookfield viscosity at -26 C	ASTM D2983	mPa.s	120000
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®