

# LIFE EXTENSION

## 85W140 GL 5

*This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.*

### APPLICATIONS

*Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.*

### FEATURES

*Frictional properties : easy gear shifting.*

*Anti-wear protection : long transmission life.*

### SPECIFICATION LEVEL

<b>API</b>	GL-5	<b>ZF</b>	TE-ML 17B
<b>MIL</b>	MIL-L-2105 C	<b>ZF</b>	TE-ML 19B
<b>MIL</b>	MIL-L-2105 D	<b>ZF</b>	TE-ML 07A
<b>ZF</b>	TE-ML 05A	<b>ZF</b>	TE-ML 16B
<b>ZF</b>	TE-ML 12E	<b>ZF</b>	TE-ML 16C
<b>ZF</b>	TE-ML 16D		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.908
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	367
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	26.1
Viscosity index	ASTM D2270		95
Pour point	ASTM D6892	°C	-15
Copper corrosion	ASTM D130		1B
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION**<sup>®</sup>