

LIFE EXTENSION

85W140 LS GL 5

Mineral oil composed of paraffinic base oils and selected additives based on sulfur-phosphorus. A special friction additive imparts to this oil the necessary properties to be used in differentials, which are equipped with a "limited-slip" mechanism.

APPLICATIONS

This oil is mainly used in all hypoid rear axles with a limited-slip mechanism.

FEATURES

Frictional properties : easy gear shifting.

Anti-wear protection : long transmission life.

SPECIFICATION LEVEL

API	GL-5	MIL	MIL-L-2105 D
MIL	MIL-L-2105 C		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.905
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	415
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	26.5
Viscosity index	ASTM D2270		86
Pour point	ASTM D6892	°C	-18
Brookfield viscosity at -12°C	ASTM D2983	mPa.s	100000
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION[®]