

# AGRILINE CHAIN SAW

*This is a very strongly adhesive oil based on mineral oils and an adhesion improver. It was specifically developed for the lubrication of chainsaws, where high demands are made. Warning : never use in the engine.*

## APPLICATIONS

*It is used primarily for the lubrication of chains saws. Due to its excellent adhesion ability it can also be used for the lubrication of conveyor chains and textile machinery.*

## FEATURES

*Stickyness : strong adhesive power.*

## SPECIFICATION LEVEL

**ISO** 6743/1

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.890
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	180
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	16,5
Viscosity index	ASTM D2270		96
Pour point	ASTM D6892	°C	-9
Flash Point COC	ASTM D92	°C	265

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**