

V TWIN 4T 20W50

This high quality mineral motorcycle oil has been exclusively developed and tested for V-Twin engines (e.g. Harley Davidson). Its unique additive package helps prevent engine wear and ensures the engine to run cooler, cleaner, and free of sludge, varnish and corrosion. V-Twin motorcycles operate at higher temperatures than water-cooled engines, so a specific high temperature additive package is necessary to protect the engine.

APPLICATIONS

Originally developed and tested exclusively for use in V-Twin engines (e.g. Harley Davidson), this oil can also be used in older 4-stroke motorcycles. It is suitable for integrated gearboxes or wet clutch systems.

FEATURES

Engine protection : excellent engine performance.

Anti-wear and oxidation stability : adequate protection of systems.

SPECIFICATION LEVEL

API	SG/CD	JASO	MA2
CCMC	G4/D2	MIL	MIL-L-46152 E

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.891
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	158
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	17.7
Viscosity index	ASTM D2270		123
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	5.5
Pour point	ASTM D6892	°C	-24
Sulfated Ash	ASTM D874	Mass %	0.6
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION[®]