

SNOW SCOOTER 4T 0W40 ESTER

This is a full synthetic, ester-based engine oil for 4-stroke engines, specifically adapted for snowmobiles for normal and intensive usage. It provides very high lubricating capacity and assures maximum power output of the engine, simultaneously reducing wear and extending the life of the engine. Viscosity fluctuations with temperature variations are minimal, thus creating less friction in the engine. This enhances the power-output and fuel economy of your snowmobile. This oil is specially adapted for very low temperatures.

APPLICATIONS

This engine oil is specifically developed for 4-stroke snowmobiles with a high power-output for normal to intensive usage. This oil is adapted for very low temperatures.

FEATURES

*Total engine protection: performance in keeping the engine clean.
Cold start : excellent fluidity at low temperature.*

SPECIFICATION LEVEL

| | | | |
|-------------|----|-------------|-----|
| API | SL | JASO | MA2 |
| JASO | MA | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.855 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 81.9 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 14.5 |
| Viscosity index | ASTM D2270 | | 185 |
| B.N. (HClO ₄ method) | ASTM D2896 | mg KOH/g | 6.6 |
| Pour point | ASTM D6892 | °C | -45 |
| Sulfated Ash | ASTM D874 | Mass % | 0.80 |
| Flash Point COC | ASTM D92 | °C | 222 |
| CCS viscosity at -35°C | ASTM D5293 | mPa.s | 5800 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION[®]