

RACING 4T 15W50 ESTER

This is a full synthetic lubricant based on carefully selected very high quality base oils for 4-stroke engines, specifically used for competition in very severe circumstances (circuit, cross, enduro, quads). It offers exceptional lubricating power, lowers oil consumption and reduces friction and wear, thereby enhancing the performance and lifetime of your motorcycle.

APPLICATIONS

This motor oil was specifically developed for motorcycle sports (road and competition), but can also be used for less heavy duty engines in city traffic and on the road. Qualified for engines with integrated gearboxes without any danger for slipping of the clutch. Resists high temperatures and reduces deposits.

FEATURES

Engine protection : outstanding engine cleanliness and durability.

Anti-wear and oxidation stability : superior protection.

Temperature stability : very high stability.

SPECIFICATION LEVEL

API	SL	JASO	MA2
JASO	MA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.854
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	124
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	18.0
Viscosity index	ASTM D2270		162
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	6.6
Pour point	ASTM D6892	°C	-36
Flash Point COC	ASTM D92	°C	260

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®