CHRONO **4T 10W40**

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil is for 4-stroke engines for normal and intensive use. Based on an enforced formula with extreme pressure additives for gear boxes. Its special formulation avoids slipping of the wet clutches and has excellent dispersant and detergent action. It offers optimum protection and longer lifetime of the engine.

APPLICATIONS

This motoroil is qualified for normal and fast driving in city traffic and on the highway and can be used for all types of motorcycles: road, cross/trial, enduro, quads.

FEATURES

Engine protection: outstanding engine cleanliness and durability.

Anti-wear and oxidation stability: superior protection. Temperature stability: superior viscosity stability.

SPECIFICATION LEVEL

API SL JASO MA2

JASO MA

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.876
Kinematic viscosity at 40°C	ASTM D445	mm²/s	91
Kinematic viscosity at 100°C	ASTM D445	mm²/s	14.1
Viscosity index	ASTM D2270		160
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	6.6
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	5600
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION