

PRO SCOOTER 4T 5W40

This is a full synthetic lubricant based on carefully selected very high quality base oils for 4-stroke engines, specifically adapted to scooters for normal and intensive usage. It provides very high lubricating capacity and assures maximum power output of the engine, simultaneously reducing wear and extending the life of your scooter. Viscosity fluctuations with temperature variations are minimal, thus creating less friction in the engine. This enhances the power-output and fuel economy of your race bike. This oil easily resists high temperatures and reduces deposits.

APPLICATIONS

This engine oil is specifically developed for scooters with a high power-output for normal to intensive usage. It is suitable for scooters with integrated gearbox or not, wet or dry clutch.

FEATURES

Engine protection : outstanding engine cleanliness and durability.

Anti-wear and oxidation stability : superior protection.

Temperature stability : very high temperature stability.

SPECIFICATION LEVEL

API	SL	JASO	MA2
JASO	MA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	80
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.1
Viscosity index	ASTM D2270		183
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	5.6
Pour point	ASTM D6892	°C	-42
CCS viscosity at -25°C	ASTM D5293	mPa.s	3430
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION[®]