

CHRONO 2T

This is a full synthetic lubricant based on carefully selected very high quality base oils for air cooled 2-stroke gasoline engines. This oil is specifically designed for two-stroke engines of motorcycles with mixed or separate lubrication. It assures a remarkable cleanliness of the engine, and has a high lubricity and a high thermal stability. It substantially avoids the formation of exhaust smoke.

APPLICATIONS

This is a 2-stroke engine oil for high performances and sportive driving. Qualified for all types of 2-stroke engines : motorcycles, scooters and racing replica. Dosage: 2 to 4%, according to the manufacturer's recommendations.

FEATURES

Engine protection : outstanding engine cleanliness and durability.

Smoke suppression : excellent smoke reduction.

Corrosion protection : adequate corrosion protection.

SPECIFICATION LEVEL

API	TC	JASO	FC
ISO	L-EGD	JASO	FD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	72.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.8
Viscosity index	ASTM D2270		138
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	1.2
Flash Point COC	ASTM D92	°C	100

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®