

SCOOTER 2T

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil is intended for the lubrication of 2-stroke gasoline engines for start-stop circumstances in city traffic. The use of this oil ensures an optimum protection against wear, even at high temperatures. The use of synthetic components reduces the formation of smoke, and keeps the exhaust system perfectly clean.

APPLICATIONS

This quality is specifically recommended for the use in scooters. Also suitable for motorbikes. Dosage: between 2 and 4%, according to the manufacturer's recommendations. Easily miscible with gasoline. May also be used for separate lubrication. Efficient protection against spark-plug fouling and avoids piston ring sticking.

FEATURES

*Engine protection : excellent engine performance.
Smoke suppression : excellent smoke reduction.
Corrosion protection : adequate corrosion protection.*

SPECIFICATION LEVEL

API	TC	JASO	FC
ISO	L-EGD	JASO	FD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.872
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	76.8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.4
Viscosity index	ASTM D2270		120
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	1.7
Flash Point COC	ASTM D92	°C	106

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION[®]