

# ACTIVE DEFENCE

## ATF F/G

**ATF TYPE F/G oil has been specifically designed for use in automatic FORD-transmissions (GLIDE). It is characterized by its very high viscosity index and low pour point, which ensure optimal performance in a broad temperature range.**

### APPLICATIONS

ATF TYPE F/G is specifically intended for use in automatic gear boxes of FORD-passenger cars. It can also be used in some other makes, for which an equal product as the FORD-specifications prescribed.

### FEATURES

Anti-wear protection : long transmission life.

Extended oil life : optimized thermal and oxidation stability.

### SPECIFICATION LEVEL

<b>FORD</b>	ESW-M2C33-F	<b>JD</b>	JDM J21A
<b>FORD</b>	ESP-M2C33-G	<b>VOLVO</b>	97330
<b>FORD</b>	SQM2-9007-AA		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Density at 15°C	ASTM D4052	g/ml	0.869
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.3
Viscosity index	ASTM D2270		173
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	30000
Flash Point COC	ASTM D92	°C	206
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**