OEM SPECIFIC ATF MB

This is a full synthetic lubricant based on carefully selected very high quality base oils, mainly intended for all MB 7-speed automatic transmissions and NAG-V Sport transmissions. It provides excellent frictional durability and superior performance.

APPLICATIONS

This ATF is recommended for the 7G-Tronic and 5-Speed automatic transmissions of Mercedes-Benz. Due to its specific composition and characteristics, it is not suitable for other applications.

FEATURES

Anti-wear protection : significantly extended transmission life. Frictional properties : very smooth gear shifting, no vibration. Extended oil life : excellent thermal and oxidation stability.

SPECIFICATION LEVEL

MB

TYPICAL CHARACTERISTICS

236.14

| Test | Method | Unit | Average result |
|-------------------------------|------------|-------|----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.848 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 28.6 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 5.9 |
| Viscosity index | ASTM D2270 | | 154 |
| Pour point | ASTM D6892 | °C | -45 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | 11800 |
| Flash Point COC | ASTM D92 | °C | 206 |
| Colour | VISUAL | | RED |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

