

# ECO FLOW

## MULTI VEHICLE ATF FE

*This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.*

### APPLICATIONS

*Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque converters for most passenger cars, off-road vehicles and SUVs.*

### FEATURES

*Frictional properties : very smooth gear shifting, no vibration.*

*Anti-wear protection : significantly extended transmission life.*

*Extended oil life : excellent thermal and oxidation stability.*

### SPECIFICATION LEVEL

<b>AISIN-WARNER</b>	JWS 3324	<b>HYUNDAI</b>	SPH-IV
<b>AISIN-WARNER</b>	AW-1	<b>JAGUAR</b>	02JDE26444
<b>BMW</b>	M-1375.4	<b>LAND ROVER</b>	LR023288
<b>BMW</b>	83222152426	<b>MAZDA</b>	FZ
<b>CHRYSLER</b>	68157995AA	<b>MB</b>	236.12
<b>FIAT</b>	9.55550-AV2	<b>MITSUBISHI</b>	ATF J3
<b>FIAT</b>	9.55550-AV5	<b>NISSAN</b>	MATIC-S
<b>FORD</b>	MERCON SP	<b>TOYOTA</b>	AUTO FLUID WS
<b>FORD</b>	MERCON LV	<b>VW</b>	G 055 162
<b>FORD</b>	WSS-M2C924-A	<b>VW</b>	G 060 162
<b>HONDA</b>	DW-1	<b>VW</b>	G 055 005
<b>HYUNDAI</b>	NWS-9638 TS	<b>VW</b>	G 055 540
<b>HYUNDAI</b>	SP-IV		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm²/s	29.4
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.1
Viscosity index	ASTM D2270		162
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	9500
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		RED

#### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**