

ECO FLOW CVT FLUID

This is a full synthetic lubricant based on carefully selected very high quality base oils, that has been designed to be used in most CVT gearboxes. It is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

OEMs usually recommend specific CVT fluids for their transmissions. By carefully balancing base oils and advanced additives, it has become possible to formulate this fluid that meets the requirements of both European and Japanese CVT manufacturers. This product may not be used in some hybrid vehicles, requiring special fluids.

FEATURES

Anti-wear protection : significantly extended transmission life.

Frictional properties : very smooth gear shifting, no vibration.

Extended oil life : excellent thermal and oxidation stability.

SPECIFICATION LEVEL

AUDI	TL 52180	MB	236.20
DAIHATSU	AMIX CVTF DFE	MINI	EZL799A
DAIHATSU	AMIX CVTF-DC	MITSUBISHI	CVTF-J1/SP-III
FORD	WSS-M2C928-A	MITSUBISHI	CVTF J-4
FORD	CVT23	NISSAN	NS-1/NS-2/NS-3
FORD	CVT30	SUBARU	ECVT
FORD	MERCON C	SUBARU	Lineartronic CVTF
GM	SATURN DEX-CVT	SUBARU	i-CVT
HONDA	HCF-2	SUZUKI	CVTF GREEN 2
HONDA	HMMF	SUZUKI	TC/NS-2/CVT Green 1
HYUNDAI	SP-CVT1	TOYOTA	TC
HYUNDAI	SP-III	TOYOTA	CVT FE
JEEP	NS-2/CVTF+4	VW	G 052 180
KIA	SP-III	VW	G 052 516

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	34.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.35
Viscosity index	ASTM D2270		189
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	10600

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®