

COMPRESSOR OIL

ISO 32

This is a compressor oil made of highly refined base oils and additives to prevent oxidation, corrosion and foaming. It meets the strict requirements of the PNEUROP-oxidation test.

APPLICATIONS

This oil is particularly recommended for the lubrication of air compressors with high temperatures or when an oil according to the DIN classification VDL is required.

FEATURES

Anti-wear and oxidation stability: superior protection.

Anti-foam properties: adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51352
DIN VDL

PNEUROP DIN 51.352

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.873
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	32.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	5.4
Viscosity index	ASTM D2270		99
A.N. (Colorimetric)	ASTM D974	mg KOH/g	0.08
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®