

# CENTRAL HYDRAULIC FLUID

*This is a full synthetic lubricant based on carefully selected very high quality base oils. It is a hydraulic "multipurpose" fluid specifically designed for the use in all circuits and in a temperature range between -40°C and 130°C. This fluid has a very high viscosity index, an exceptional oxidation stability, anti-foam and anti-rust properties. It has a unique friction reducing additive for reduction of wear and noise production of the hydraulic pump.*

## APPLICATIONS

*This multipurpose fluid is to be used in the following applications : hydraulic suspensions, shock absorbers, hydrostatic controls, centralized hydraulic circuits, power steering and level controls. It is also suitable for suspension and steering wheel systems of MAN trucks.*

## FEATURES

*Pour point : excellent low temperature properties.*

## SPECIFICATION LEVEL

<b>CHRYSLER</b>	MS 5931	<b>SAAB</b>	9-3 power steering
<b>FORD</b>	WSS-M2C204-A	<b>SAAB</b>	9-5 power steering
<b>GM</b>	9985835	<b>VOLVO</b>	1161529-1
<b>MAN</b>	M3289	<b>VW</b>	TL 521.46
<b>MB</b>	345.0	<b>ZF</b>	TE-ML 02K
<b>OPEL</b>	GM 1940766	<b>ZF</b>	TE-ML 09B

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average result
Color	ASTM D1500		green
Density at 15°C	ASTM D4052	g/ml	0.823
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	19.2
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6,3
Viscosity index	ASTM D2270		322
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	840
Flash Point COC	ASTM D92	°C	156

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION**<sup>®</sup>