

ALL-PURPOSE EP NR. 0

This is a semi-liquid Lithium grease. It has an excellent low temperature pumpability, maintaining its good flow property. By the use of "Extreme Pressure" additives, this grease is resistant to heavy shocks and loads. It has also excellent anti-corrosion, anti-rust and anti-oxidant-properties, which increase the life span of the grease and the lubricated parts.

APPLICATIONS

This grease is specifically designed for central lubricating units, like those used for industrial machines and trucks.

FEATURES

Low temperature properties : excellent pumpability.

Extreme pressure properties : superior EP action.

SPECIFICATION LEVEL

ISO	6743	DIN	51502
ISO	L-XCCFBO	DIN	KPOK-30

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Texture	Visual		Smooth
Colour	VISUAL		Yellowish Brown
NLGI Classification	ASTM D217		0
Worked Penetration (60 strokes)	ISO 2137	0.1 mm	370
Dropping point	ISO 2176/IP 396	°C	170
Four Ball Weld Load	ASTM D2596/ DIN51350:4	N	2600

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®